



# USB 1.1 Rover<sup>®</sup> 1850

## 1-Port USB 1.1 85m\* CAT 5e/6/7 Extender System

The Rover 1850 extends USB 1.1 connections beyond the desktop up to 85\* meters.

LEX (Local Extender)



Actual cable length  
45.7cm (18")

REX (Remote Extender)



Actual cable length  
15.2cm (6")



4664 Lougheed Hwy.  
Suite 221  
Burnaby, BC,  
V5C 5T5, Canada

www.icron.com  
+1 604 638 3920

## Features

The Rover 1850 uses technology ideal for extending USB peripherals including: keyboards, mice, interactive white boards, and game controllers and does not require external power adapters. Key features include:


- Remote extender supplies up to 400mA\*\* to USB devices
- Supports both full-speed (12Mbps) and low-speed (1.5Mbps) throughputs
- Reliable operation with all USB 2.0 and 1.1 devices, including hubs
- Robust ESD and EFT immunity for industrial environments
- 3-year warranty

Includes the ExtremeUSB<sup>®</sup> suite of features:

- Transparent USB extension
- True plug and play; no software drivers required
- Works with all major operating systems: Windows<sup>®</sup>, macOS<sup>™</sup>, Linux<sup>®</sup> and Chrome OS<sup>™</sup>

## Applications

- Interactive white board
- Keyboard and mouse
- Sensor/data acquisition
- Industrial control



Specifications subject to change  
without notification.

©2022

Icron | An Analog Devices Brand  
#90-00874-D01

\* Up to 40m for all USB devices; 85m is achievable for most low powered HID USB devices.

\*\* 400mA when LEX is supplied with 700mA



## RANGE

Full-Speed and Low-Speed:	Up to 40m (131 ft)
Low-Speed:	Up to 85m (279 ft)*

## LEX (LOCAL EXTENDER)

USB Connector:	1 x USB Type A Plug
Pig Tail Length:	45.7cm (18")
Link Connector:	1 x RJ45
Dimensions:	85mm x 40mm x 22mm (3.34" x 1.57" x 0.87")
Enclosure Material:	Black ABS

## REX (REMOTE EXTENDER)

USB Connector:	1 x USB Type A Receptacle
Pig Tail Length:	15.2cm (6")
Link Connector:	1 x RJ45
Maximum Current Available:	400mA when LEX is supplied with 700mA
Dimensions:	85mm x 40mm x 22mm (3.34" x 1.57" x 0.87")
Enclosure Material:	Black ABS

## ENVIRONMENTAL

Operating Temperature:	0°C to 50°C (32°F to 122°F)
------------------------	-----------------------------

## COMPLIANCE

Certifications:	FCC (Class A), CE (Class A), RoHS2/3 (CE), ICES-003 Issue 7, EN 62368-1, CPSIA, Flammability V-1
-----------------	--

## SUPPORT

Warranty:	3-year
-----------	--------



\* device and host dependant

## Ordering Information

The USB 1.1 Rover® 1850 system includes a LEX, REX, Quick Start Guide and three-year warranty.

For more information, contact us at [www.icron.com/contact](http://www.icron.com/contact) or call +1 604 638 3920.

PART #	NAME	DESCRIPTION
00-00301	USB 1.1 Rover® 1850	1-Port 85m CAT 5e/6/7 Bus-Powered USB Extender System